

SPECIFICATIONS FOR 48" SERIES PLATFORM/STAKE & VAN CABLE LIFTGATES 1,300 LB. CAPACITY

2/09

I. LIFTGATE FEATURES

- A. Lifting capacity: 1,300 lbs
- B. Maximum bed height: 48"
- C. Electrical connections: Electrical power source is supplied through the vehicle's parking lights. The liftgate is wired via the license plate light wires on the truck. Turning off the parking lights will prevent unauthorized operation of liftgate. The liftgate will not operate without the parking lights in the "ON" position. A 150-amp heavy-duty circuit breaker with manual reset is furnished to protect the battery and electrical system on the vehicle.
- D. Control switch: The control switch is mounted on the curbside of the truck. It is mounted on the outside of the upright and up high enough to be inaccessible to small children. The gate is controlled with a 3-way toggle switch; up-neutral-down.
- E. Plated cylinder shaft: chrome plated cylinder shaft to help prevent rusting
- F. Hydraulics:
 - 1. All hydraulics are totally enclosed in the housing of the liftgate for weather protection.
 - 2. Electric/hydraulic power unit has a built-in relief valve to prevent overloading of the liftgate while raising.
 - 3. An in-line flow control valve on the cylinder helps control the speed of the oil coming out of the cylinder returning to the reservoir when lowering the liftgate under loaded conditions.
- G. Drop-away platform: platform of liftgate will "drop-away" for easy dock and forklift loading direct into truck bed.
- H. Gates are painted in black electrocoat topcoat.

II. LIFTGATE SPECIFICATIONS

- A. Liftgate housing: 8 ga. steel front and 10 ga. steel rear
- B. Upright housing: 10 ga. upright steel
- C. Reinforced single-wall platform:
 - 12 ga. TPX steel load skin
 - Five - 10 ga. vertical reinforcing channels run the full height of the platform

SPECIFICATIONS FOR 48" SERIES PLATFORM/STAKE & VAN CABLE LIFTGATES 1,300 LB. CAPACITY

2/09

- D. Platform floor surface area:
 - E48-64 = 62" wide x 34" deep w/tapered ramp
 - E48-72 = 68" wide x 34" deep w/tapered ramp
 - E48-78 = 76" wide x 34" deep w/tapered ramp
 - E48-86 = 82" wide x 34" deep w/tapered ramp
 - E48-91 = 86" wide x 34" deep w/tapered ramp
- E. Platform support links: 1/4" x 1-1/4" steel support links connect the platform to gate frame for loading surface support
- F. Platform latches: latches located at the top of the uprights are spring loaded and quick release
- G. 7/8" dia. "D" hole pins with snap rings for arm pins
- H. Liftgate cable: 1,300 lb. capacity liftgates have 1/4" dia., 6 x 36 (WS) stranded cables
- I. Pulleys: upright pulleys are 4" dia. and housing pulleys are 4-1/2" dia.
- J. Cylinder: cylinder has 1-3/4" bore with 17-3/8" stroke with 4-1/2" dia. pulley
- K. Composite bushings: maintenance free bushings at all pivot points to eliminate the need for grease zerks and necessity of lubrication
- L. All retaining pins for pulleys, lift arms, cylinder trunnion and lift cables are to be retained by snap rings, not rivets, for easy accessibility

III. LIFTGATE OPTIONS

- A. 2-button hard wired hand-held control system with plug-in
- B. Recessed light kits available on E48-78, E48-86 and E48-91 models
- C. Grated platform (deck span surface) is available as a platform option
- D. Aluminum treadplate platform
- E. Audible safety alarm
- F. Rhino Linings Tuff Stuff® is available as a platform option
- G. Zinc plating is available as a platform option